



CONTROL CHARACTERISTICS		
	MANDATORY MEASUREMENT	
	FIT/FUNCTION SPC	
	SAFETY CHARACTERISTIC	



3 CORD STREET  
 DUDLEY PARK SA 5008  
 Ph: (08) 8269 4000  
 Fax: (08) 8269 4000  
 www.roycecross.com.au

PROJECTION	DRAFTING STANDARD AS 1100	SIZE A4
ALL DIMENSIONS ARE IN mm UNLESS OTHERWISE SPECIFIED		
TOL. 1 PLACE DECIMAL $\pm 0.25$ ANGLE $\pm 0.30^\circ$		
2 PLACE DECIMAL $\pm 0.13$		
MATL	SPEC	

TITLE			
DRIP PROOF - SPLIT PHASE - 1400RPM (B56 215ML)			
DRN	NL	DATE	12.01.09
CHK		APPD	
SCALE	NTS		

USED	NO	FR M56 WITH STANDARD FOOT	
KW	0.25	HP	1/3
PART NO	S.25C4SCG	AMPS	3.00
TYPE SPLIT PHASE OPEN DRIFT PROOF			
CAP RUN	-	CAP START	-

BRAND	
DRG NO	S.25C4SCG
REV	
CODE No.	