


TERMINAL BOX TAPPED FOR 20mm CONDUIT

CONTROL CHARACTERISTICS		
◻ MANDATORY MEASUREMENT	◊ FIT/FUNCTION SPC	△ SAFETY CHARACTERISTIC



DETAIL AT 'A' SCALE 1:1



3 CORD STREET
DUDLEY PARK SA 5008
Ph: (08) 8269 4000
Fax: (08) 8269 4000
www.roycecross.com.au

PROJECTION	DRAFTING STANDARD AS 1100	SIZE A4
ALL DIMENSIONS ARE IN mm UNLESS OTHERWISE SPECIFIED		
TOL. 1 PLACE DECIMAL ± 0.25 ANGLE ± 0.30°		
2 PLACE DECIMAL ± 0.13		
MATL	SPEC	

TITLE			
TOTALLY ENCLOSED CAPACITOR START - 1400RPM (B56 295ML)			
DRN	NL	DATE	2.12.08
CHK		APPD	
SCALE	NTS		

USED ON	FRAME 56	
KW	0.75	HP 1.0
PART NO	S.75B4CCG	AMPS 6.0
TYPE	TEFC CAP START/ CAP RUN	
CAP RUN	10	CAP START 120

BRAND	Crompton Greaves	
DRG NO	S.75B4CCG	
REV		
CODE No.		