



TERMINAL BOX POSITION : - CAN BE ARRANGED AT EITHER 9, 12 OR 3 O'CLOCK BY MOV
 STANDARD TERMINAL BOX POSITION IS 3 O'CLOCK AS SHOWN.
 CONDUIT ENTRIES:- TERMINAL BOX CAN BE ROTATED AT 90° INTERVALS
 (CONDUIT ENTRY POSITION SHOWN FOR ILLUSTRATION ONLY).



3 CORD STREET
 DUDLEY PARK SA 5008
 Ph: (08) 8269 4000
 Fax: (08) 8269 4000
 www.roycecross.com.au

PROJECTION	DRAFTING STANDARD AS 1100	SIZE A3
ALL DIMENSIONS ARE IN mm UNLESS OTHERWISE SPECIFIED		
TOL. 1 PLACE DECIMAL ± 0.25 ANGLE ± 0.30°		
2 PLACE DECIMAL ± 0.13		
MATL	SPEC	

TITLE			
OUTLINE DIMENSION DRAWING W ALUMINIUM TOTALLY ENCLOSED FAN COOLED 132S/M FRAME FOOT MOUNTED MOTOR			
DRN	NL	DATE	06.03.09
CHK		APPD	
SCALE	NTS		

USED ON	D132S/M	
KW	HP	
PART NO	AMPS	
TYPE		
CAP RUN	CAP START	

BRAND	Crompton Greaves	
DRG NO	D132S/MCG	REV
CODE No.		