



HOLE TAPPED M8 x 19 DEEP TO DIN 332 FORM D

VIEW ON 'X'

TERMINAL BOX POSITION:- CAN BE ARRANGED AT EITHER 9,12 OR 3 O'CLOCK BY MOVING  
 STANDARD TERMINAL BOX POSITION IS 3 O'CLOCK AS SHOWN.  
 CONDUIT ENTRIES:- TERMINAL BOX CAN BE ROTATED AT 90° INTERVALS  
 (CONDUIT ENTRY POSITION SHOWN FOR ILLUSTRATION ONLY).



3 CORD STREET  
 DUDLEY PARK SA 5008  
 Ph: (08) 8269 4000  
 Fax: (08) 8269 4000  
 www.roycecross.com.au



DRAFTING STANDARD AS 1100

SIZE A3

ALL DIMENSIONS ARE IN mm UNLESS OTHERWISE SPECIFIED  
 TOL. 1 PLACE DECIMAL ± 0.25 ANGLE ± 0.30°  
 2 PLACE DECIMAL ± 0.13

TITLE OUTLINE DIMENSION DRAWING W ALUMINIUM TOTALLY ENCLOSED FAN COOLED D90S/L FRAME FOOT MOUNTED MOTOR

DRN	NL	DATE	06.03.09
CHK		APPD	
SCALE	NTS		

USED ON	D90S/L	
KW	HP	
PART NO	AMPS	
TYPE		
CAP RUN	CAP START	

BRAND		
DRG NO	D90SLCG	REV
CODE No.		